

SNL48V25 SPECIFICATION SHEET



*SNL12V125BT Shown For Physical Comparison Only

About Invicta Lithium

The Invicta Lithium 48V range has been specifically designed for replacement of similar size Lead acid batteries. The family is comprised of the popular sizes found in the lead acid range but with the added benefits of Lithium Iron Phosphate (LiFePO₄) technology and is ideally suited to deep cycle longer run time applications.

Features & Benefits

- Large number of cycles >2000 (100% DoD)**
 Up to 8 times cycle life of SLA lowering your total cost of ownership
- Safe and stable chemistry & Integrated BMS**
 The use of LiFePO₄ along with the integrated BMS ensures protection against over charge / discharge, temperature and short circuit providing the highest degree of safety
- Greater capacity utilisation - 60% more than SLA**
 Gives longer runtime than equivalent SLA
- High energy density (less than half of the weight of SLA)**
 Lowering total weight of application
- Fast recharge**
 Battery is charged and ready to be used sooner
- Flat Discharge Curve**
 Longer run time & more efficient use of capacity
- Extremely low self-discharge rate**
 Can sit unused for longer periods of time
- UL1642 at cell level**

Nominal Voltage	51.2v
Nominal Capacity (25°C, 0.33C)	25Ah
Terminal	M8
Length (mm)	318 ± 2mm
Width (mm)	165 ± 2mm
Height (mm)	215 ± 2mm
Weight	12.2kg
Max Charge Voltage	58.4 ± 0.1V
Standby	55.2 ± 0.1V
Cut off Voltage	40V
Max. Discharge Current	50A
Max. Pulse Discharge Current (3 Sec)	115A
Max. Charge Current	25A
Recommended Current Charge	≤12.5A
Cycle Life (100% DoD)	≥2000
Operating Temp - Charge	0 - 50°C
Operating Temp - Discharge	-20 - 55°C
Short Circuit Release	Load Release
Max. Series / Parallel Configuration	4P
Bluetooth Connectivity	No

Terminal M8 Insert

